

HAND PROTECTION

ARAX FOOD GRADE CUT RESISTANT LINER

PRODUCT DATA SHEET: AL-(SIZE)

PRO
PRO CHOICE SAFETY GEAR

PRODUCT CODE:
AL-(SIZE)

*Image is representative only



FEATURES AND BENEFITS

- Certified to EN 420/AS/NZS2161.2:2005 General Requirements.
- Certified to EN 388/AS/NZS2161.3:2005 Protection Against Mechanical Risks.
- EN388:2016 Cut Resistance Level "D".
- ISO Cut Resistant Level D.
- Food Contact Approved according to Directive 2002/72/EC.
- CE Category II Glove.
- The 13 Gauge Arax Liner is a lightweight Basalt, Polyethylene, Polyester fibre which offers outstanding protection against cuts and abrasion. In addition to providing outstanding flexibility and comfort to the end-user.
- Machine washable for re-use.
- No Glass fibre to contaminate food sources.
- Approved for use in food handling industries - HACCP Approval.

PHYSICAL DIMENSIONS

SIZE	PALM WIDTH	GLOVE LENGTH
7	9.3cm +/-	23.0cm +/-
8	9.8cm +/-	24.0cm +/-
9	10.3cm +/-	25.0cm +/-
10	10.8cm +/-	26.0cm +/-
11	11.3cm +/-	27.0cm +/-
12	11.5cm +/-	28.0cm +/-

PRODUCT DETAILS

Material: 13 gauge Seamless (Basalt, PE, Polyester)

APPLICATIONS

The Pro Choice Safety Gear range of hand protection is ideal for protection against risks associated with a wide range of applications in both workplace and recreational environments.

Typical applications include but are not limited to: Abattoirs, butchers, meat and fish processing, vegetable processing, blade sharpening and cleaning, and general purpose materials handling. Can be used as a liner under other gloves to increase protection.



BREATHABLE



COMFORT



CUT
RESISTANT



DEXTEROUS



MACHINE
WASHABLE

AVAILABLE IN

PRODUCT CODE	COLOUR	UOM	MOQ	CTN QTY
AL	WHITE	PAIR	12	120

STANDARDS

CE CATEGORY II:

II Intermediary risk in accordance with:

EN 420/AS/NZS 2161.2:2005 General Requirements

EN388/AS/NZS 2161.3:2005 Protection Against Mechanical Risks

Results: 2X43D

HACCP Food Zone Classification (FZP)

Certificate Number: PENDING



CUT TEST - ISO13997

Amount of pressure required to make an incision over a 20mm travel distance using a razor sharp blade.

PERFORMANCE LEVEL	NEWTON	WEIGHT
A	<2	200gms
B	≥5	500gms
C	≥10	1kg
D	≥15	1.5kg
E	≥22	2.2kg
F	≥30	3.0kg

CARE INSTRUCTIONS



MACHINE
WASH



WATER
TEMP 55°C



TUMBLE
DRY



LOW
HEAT

PARAMOUNT SAFETY PRODUCTS AUSTRALIA

12 FELLOWSHIP ROAD,
GNANGARA, WA 6077

TECH SUPPORT: 1300 275 820

CUSTOMER SERVICE: 1300 770 723

EMAIL: INFO@PROCHOICESAFETYGEAR.COM

PARAMOUNT SAFETY PRODUCTS NEW ZEALAND

7 SIR WOOLF FISHER DRIVE, HIGHBROOK,
EAST TAMAKI, AUCKLAND 2013

TECH SUPPORT: 0800 888 778

CUSTOMER SERVICE: 0800 888 778

EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ

PROCHOICESAFETYGEAR.COM
PARAMOUNTSAFETY.COM

PRO
PRO CHOICE SAFETY GEAR

FROM

PARAMOUNT
SAFETY PRODUCTS