

RESPIRATORY GEAR

HORIZONTAL FLAT FOLD P2 RESPIRATOR

PRODUCT DATASHEET: PC5005

PRO
PRO CHOICE SAFETY GEAR

PRODUCT CODE:
PC5005



FEATURES AND BENEFITS

- Certified to AS/NZS 1716:2012 Respiratory Protective Devices.
- P2 disposable respirator for protection against mechanically & thermally generated particles.
- Dual latex free elastic straps for ease of donning & doffing.
- Horizontal flat fold for improved comfort & fit.
- Adjustable nose bridge and soft inner nose foam for ultimate comfort and fit.
- Easily worn with glasses & goggles.
- Resealable bag for hygienic storage.

AVAILABLE IN

PRODUCT CODE	MOQ	PACK QUANTITY	CARTON QUANTITY
PC5005	1 box	10 pieces	20 boxes

PRODUCT DETAILS

Straps:	Latex-Free Rubber Band
Nose Foam:	EVA
Nose Clip:	PP + STEEL
Filter Media:	Polypropylene Melt-Blown
Weight:	9.1G ± 1

CARE INSTRUCTIONS

Shelf life of the unopened product is 3 years from date of manufacture when stored within temperature range of -20°C to +25°C & less than 80% relative humidity.

Manufactured date printed onto filters, maximum life span is 6 months once filter is removed from original packaging, however life span is determined by the wearers ability to taste, smell or notice increase in breathing resistance.

Ensure mask is correctly fitted prior to each use & conduct annual fit testing in accordance with AS/NZS 1715:2009.



COMFORT



PARTICULATE PROTECTION



VALUE

WARNINGS AND USE LIMITATIONS

1. Facial hair has the potential to compromise the required protective seal of the respirator.
2. Ensure adequate oxygen levels are present.
3. Ensure the contamination is known and the respirator is suitable for the application.
4. Replace when taste, smell or the breathing resistance is high.
5. Store in a clean resealable storage device.

STANDARDS

CERTIFIED TO:

AS/NZS 1716:2012 Respiratory Protective Devices
Certified by SAI Global

To be used in conjunction with: AS/NZS 1715:2009 -
Selection, use & maintenance of respiratory protective equipment



AS/NZS 1716:2012
Lic SMK41114

CLASSIFICATION	EFFICIENCY	EXAMPLE OF CONTAMINANTS/USES
P1	80% (Particles to 1µm micron = 0.001mm size)	Dust
P2	94% (particles to 0.3µm micron = 0.0003mm size)	Toxic dusts including asbestos, welding fumes
P3	99.95% (particles to <0.3µm micron = less than 0.0003mm size)	Toxic dusts including asbestos, welding fumes, full face and powered air performance at P3 only

PARAMOUNT SAFETY PRODUCTS AUSTRALIA

12 FELLOWSHIP ROAD,
GNANGARA, WA 6077
TECH SUPPORT: 1300 275 820
CUSTOMER SERVICE: 1300 770 723
EMAIL: INFO@PARAMOUNTSAFETY.COM

PARAMOUNT SAFETY PRODUCTS NEW ZEALAND

7 SIR WOOLF FISHER DRIVE, HIGHBROOK,
EAST TAMAKI, AUCKLAND 2013
TECH SUPPORT: 0800 888 778
CUSTOMER SERVICE: 0800 888 778
EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ

PROCHOICESAFETYGEAR.COM
PARAMOUNTSAFETY.COM

PRO
PRO CHOICE SAFETY GEAR
FROM
PARAMOUNT
SAFETY PRODUCTS