



TRIDENT® HEXHALE® POWERED AIR PURIFYING RESPIRATOR COMPLETE BLOWER SYSTEM

WIDE APPLICATION

THE BLOWER SELF-ADJUSTS TO VARYING AIR DENSITIES, MAKING IT SUITABLE FOR HIGH ALTITUDE ENVIRONMENTS. ITS OUTER SHELL, MADE OF ANTI-ELECTROMAGNETIC MATERIAL, ALLOWS FOR SAFE USE IN MAGNETIC ENVIRONMENTS.



Australian Standard
AS/NZS 1716:2012
Lic. SMK41528



IPS DISPLAY

THE HIGHEST COLOUR ACCURACY AND WIDEST VIEWING ANGLE. COLOURS AND IMAGES REMAIN CONSISTENT FROM ANY ANGLE, ENSURING EASY READABILITY OF DEVICE INFORMATION IN ALL CIRCUMSTANCES.

INTELLIGENT AIRFLOW MONITORING

THE MOTOR AUTOMATICALLY ADJUSTS ITS POWER TO MAINTAIN A CONSTANT AIRFLOW SUPPLY, BASED ON FILTER LOADING OR REMAINING BATTERY.

3-LEVEL ADJUSTABLE AIRFLOW

ADJUST THE AIRFLOW THROUGH 3 LEVELS TO SUIT YOUR WORK REQUIREMENTS: 170/190/210L/MIN.

MULTIPLE FILTER OPTIONS

THE P3 PARTICLE FILTER CAN BE PAIRED WITH A GAS FILTER (A1B1E1K1 OR A1), OR AN ODOUR FILTER IF NO GAS FILTER IS INSTALLED, PROVIDING FLEXIBILITY TO SUIT VARIOUS WORK REQUIREMENTS.

OPTIONAL EXTENDED BATTERY

OPTIONAL EXTENDED 6400MAH HIGH CAPACITY BATTERY CAN LAST UP TO 15 HOURS.



TRIDENT® HEXHALE® POWERED AIR PURIFYING RESPIRATOR COMPLETE BLOWER SYSTEM RTC5200

FEATURES

- Airflow, Battery and Filter monitoring
- Up to 15 hours run time (with HD battery)
- Auto-alarm system
- Includes spark screen, pre filter and P3 particle filter
- Option to pair with a ABEK1, A1 and odour filter
- Fast-charging battery
- Tested and approved with RTC5203, RTC5207 and RTC5208 filters
- 3 airflow rates 170L/min, 190L/min and 210L/min
- Backpack available

AREAS OF APPLICATION

- Agriculture
- Construction
- Energy
- Industrial Particulate Filtration
- Mining
- Oil & Gas
- Painting
- Healthcare
- Pharmaceuticals
- Welding, Grinding & Sanding

SIZING


● Universal RTC5200

PACKAGING

1 per inner box
4 per carton
Carton Dimensions:
570 x 520 x 245mm

STORAGE

Blower System



STANDARDS & CERTIFICATIONS



Australian Standard
AS/NZS 1716:2012
Lic. SMK41528