

KEY TECHNOLOGY



3 Panel
Construction



Exhalation Valve



Proprietary
Foam Nose Seal



Fluid Resistant



Low Breathing
Resistance Filter



Fit Test Results



Latex Free

FEATURES

- Advanced multilayer technology providing protection against mechanically and thermally generated particulates including: dusts, mists, fumes and smoke
- Three panel design provides structural integrity, form fit seal and optimal comfort
- Proprietary adjustable foam nose pad to ensure consistent optimum facial seal and reduce fogging of eyewear
- Valved design eliminates the build up of heat and moisture within the breathing zone
- Versatile unisex fit suitable for a range of facial shapes and sizes. Effective for many "hard to fit" individuals
- Specialised TRIDENT® respirator seal attains unrivalled PortaCount® fit testing results
- Low breathing resistance, maximising wearer comfort, durability and life of product
- Designed to be used in conjunction with other mandatory personal protective equipment
- Each mask is individually batch numbered and packaged for the ultimate in traceability, portability and hygiene

AREAS OF APPLICATION

- Industrial Particulate Filtration
- Personal Hygiene & Safety



Part No: **RTCFFPV**



SIZING


Small	RTCFFP2SV
Regular	RTCFFP2V
Regular Extended Length Head Straps	RTCFFP2VE
XX Large	RTCFFP2XXLV

PACKAGING

1 mask per bag
20 masks per inner
240 masks per carton

RTCFFP2V	610 x 250 x 460mm GW: 5.5kg
RTCFFP2VE	610 x 250 x 500mm GW: 6kg
RTCFFP2XXLV	650 x 260 x 540mm

STORAGE



**STANDARDS &
CERTIFICATIONS**



CERTIFIED P2
AS/NZS 1716: 2012
ID No. BMP 732382

CERTIFIED FFP2 FFP3
EN 149:2001 + A1:2009
ID No. BMP 754423

CE 2797

UK
CA 0086



INDUSTREE.COM.AU



INDUSTREE
GROUP