

Hearing protection Ear Plugs

2125.372



uvex xact-band

- Banded disposable earplugs with reusable left and right insertion pins
- Replaceable pods for added hygiene
- Tapered earplugs that are shaped to fit into ear canals with ease
- Left and right thumb indentations on insertion pins for easy fitment
- Easy to insert even while wearing gloves
- Comfortable to wear for long periods of time
- Compliant to AS/NZS1270:2002; SLC⁸⁰ 22dB Class 4

Ear canal sizing:

SLC⁸⁰
dB
22

XA-RP



Product Details		
Part No.	2125.372	XA-RP - Replacement Pods
Barcode	4031101597577	4031101499260
Packaging	1 piece (5 pieces per box)	1 box, 250 pairs (5 pairs per mini box)
SLC ⁸⁰	22 dB, Class 4	
AS / NZ Standards	AS/NZS 1270:2002	
Storage	If the product is stored in a dry, clean environment, away from UV light and out of direct sunlight at a temperature of -20°C to +50°C and air humidity of a maximum of 90% and storage instructions have been followed, the product can be stored for up to 5 years from the date of manufacturing. The date of manufacturing can be found on the packaging	
Life Expectancy of Product	20 times / 150 hours	

Attenuation Data Freq. - frequency Mean att. Mean attenuation Std. dev. – standard deviation APV – assumed protection value							
Frequency in hertz	125	250	500	1000	2000	4000	8000
Mean att. dB	25.7	21.4	23.7	25.5	32.	39.1	37.3
Std. dev. dB	5.5	5.5	6.8	7.0	7.3	9.8	98.7
APV	19.8	15.9	16.9	18.5	25.2	29.3	28.6

Target Applications (but not limited to):

- Engineering
- Airlines / Cabin crews
- Entertainment industry
- Emergency services
- Fabrication (under welding helmet)



Hearing protector Class 4 tested to AS/NZS 1270. When selected, used and maintained as specified in AS/NZS 1269, this protector may be used in noise up to 105dB(A) assuming an 85 dB(A) criterion. A lower criterion may require a higher protector class.



CLICK or SCAN
for more information on
uvex hearing range