

Hearing protection Ear Plugs

uvex com4-fit



- Disposable earplugs
- Specifically designed for narrower and smaller ear canals
- Comfortable to wear for long periods of time
- Available in cabled and uncabled versions
- Patented x-grip technology reduces pressure in the ear canal and makes it significantly easier to remove the earplug
- Compliant to AS/NZS1270:2002; SLC⁸⁰ 22dB Class 4

Ear canal sizing:



Product Details			
Part No.	CF- CD	CF-UC	CF-PB
Barcode	4031101340586	4031101340593	4031101340616
Packaging	1 box (100 pairs cabled)	1 box (200 pairs uncabled)	1 bag (200 pairs uncabled refill bag for dispenser)
SLC ⁸⁰	22 dB, Class 4		
AS / NZ Standards	AS/NZS 1270:2002		
Storage	If the product is stored in a dry, clean environment, away from UV light and out of direct sunlight at a temperature of -20°C to +50°C and air humidity of a maximum of 90% and storage instructions have been followed, the product can be stored for up to 5 years from the date of manufacturing. The date of manufacturing can be found on the packaging		
Life Expectancy of Product	20 times / 150 hours		

Attenuation Data Freq. - frequency Mean att. Mean attenuation Std. dev. – standard deviation APV – assumed protection value							
Frequency in hertz	125	250	500	1000	2000	4000	8000
Mean att. dB	20.7	20.1	23.5	24.6	29.6	36.2	36.2
Std. dev. dB	7.8	7.8	7.9	5.1	5.3	5.5	6.5
APV	12.9	12.2	15.6	19.5	24.3	30.6	29.6

Target Applications (but not limited to):

- Construction
- Light manufacturing
- Areas where nuisance noise is present
- Manufacturing plants with medium level noise area and long term exposure



CLICK or SCAN
for more information on
uvex hearing range

Hearing protector Class 4 tested to AS/NZS 1270. When selected, used and maintained as specified in AS/NZS 1269, this protector may be used in noise up to 105dB(A) assuming an 85 dB(A) criterion. A lower criterion may require a higher protector class.