

Hearing protection Ear Plugs

uvex hi-com



- Disposable earplugs
- Optimum environment requiring low noise reduction
- Excellent for speech recognition
- Comfortable to wear for long period of time
- Compliant to AS/NZS1270:2002; SLC⁸⁰ 16dB Class 2

Ear canal sizing:

SLC⁸⁰
dB
16



Product Details		
Part No.	HC-UC	HC-PB
Barcode	4031101403960	4031101423333
Packaging	1 box (200 pairs uncorded)	1 bag (200 pairs uncorded)
SLC ⁸⁰	16 dB, Class 2	
AS / NZ Standards	AS/NZS 1270:2002	
Storage	If the product is stored in a dry, clean environment, away from UV light and out of direct sunlight at a temperature of -20°C to +50°C and air humidity of a maximum of 90% and storage instructions have been followed, the product can be stored for up to 5 years from the date of manufacturing. The date of manufacturing can be found on the packaging	
Life Expectancy of Product	20 times / 150 hours	

Attenuation Data Freq. - frequency Mean att. Mean attenuation Std. dev. – standard deviation APV – assumed protection value							
Frequency in hertz	125	250	500	1000	2000	4000	8000
Mean att. dB	14.4	14.8	16.8	19.3	27.0	28.9	28.6
Std. dev. dB	7.5	7.7	7.4	5.9	7.3	7.2	8.7
APV	6.9	7.1	9.5	13.4	19.7	21.7	19.9

Target Applications (but not limited to):

- Airlines / cabin crews
- Entertainment industry
- Emergency services
- Warehousing
- Health care
- Call centre



Hearing protector Class 2 tested to AS/NZS 1270. When selected, used and maintained as specified in AS/NZS 1269, this protector may be used in noise up to 100 dB(A) assuming an 85 dB(A) criterion. A lower criterion may require a higher protector class.



CLICK or SCAN
for more information on
uvex hearing range