

Hearing protection Earmuffs



uvex K200 (page 1 of 2)

- Dielectric ear muffs with length adjustment
- Suitable for use in workplace environments with exposure to electrical voltage
- Adjustable headband for a perfect fit optimum protection
- Easily adjustable for a customised fit
- Range of positions possible with 360° capsule rotation
- Approved to AS/NZS 1270:2002 - SLC80:28dB, Class 5

SLC80
dB
28



Part Number/Barcode:

- 2610.200 - uvex K200 dielectric earmuff with adjustable headband, black/ yellow, SLC80:28dB, Class 5
- Barcode - 4031101638140

Packaging:

- 1 unit per box
- 20 units per carton

Accessories:

- 2599.971 - uvex K series hygiene kit - 2 sealing cushions, 2 noise insulating foam pads



2599.972

Hearing protection Earmuffs

uvex K4 (page 2 of 2)

Product Details							
Colour		Black/Yellow					
Part No.		2610.200					
Design		With 360° headband rotatable					
SLC ₈₀		28 dB, Class 5					
Clamping force		11,6N 11,6N 12N					
Weight		168g					
Packing		1 unit					
Storage		Storage location, in original packaging, dry, clean, protected from light, UV and heat. UV and heat protected in the temperature range -10°to 55 °C, humidity max. 85%. Storage period 5 years, from date of manufacture. (Date of manufacture see product or packaging) Make sure that during storage the stirrup is not stretched, and the sealing pads are not compressed.					
Life Expectancy of Product		Service life 5 years, from date of manufacture. Recommendation: Regular replacement of the sealing pads extends the service life. Dispose of the product after expiry or immediately if it is damaged or can no longer be cleaned.					
Certified standards							
AS / NZ Standards		AS/NZS 1270:2002					
European Standard		EN 352-1:2020					
Attenuation Data							
Frequency in Hertz	125	250	500	1000	2000	4000	8000
Mean att. dB	15.1	16.6	25.7	32.7	35.2	38.8	39.8
Std. dev. dB	4.6	3.2	3.7	2.8	2.9	3.3	3.7
APV	10.5	13.4	22.0	29.9	32.3	35.5	36.1

Freq. - frequency
Mean att. - mean attenuation
Std. dev. - standard deviation
APV - assumed protection value

- Hearing protector Class 5 tested to AS/NZS 1270. When selected, used and maintained as specified in AS/NZS 1269, this protector may be used in noise up to **105dB(A)** assuming an **85 dB(A)** criterion. A lower criterion may require a higher protector class.

UVEX SAFETY AUSTRALIA LIMITED PARTNERSHIP

Unit 3 Riverside Centre, 24-28 River Road West, Parramatta NSW 2150, Australia
T 1800 815 790 E info@uvex.com.au
uvex-safety.com.au

UVEX Safety New Zealand Ltd

T +64 800 698 839 E info@uvex.co.nz
uvex-safety.co.nz



CLICK HERE or
SCAN QR code
for more information on
uvex hearing range