

Hearing protection Earmuffs



uvex K3 (page 1 of 2)

- Earmuffs with length adjustment
- Lightweight with a small cup
- Easily adjustable for a perfect fit
- Padded headband and sealing cushions for optimum wearer comfort
- Approved to AS/NZS 1270:2002 - SLC80:33dB, Class 5

SLC80
dB
33



Part Number/Barcode:

- 2610.003 - uvex K3 length adjustment earmuff, black/red, SLC80:33dB, Class 5
- Barcode - 4031101638133

Packaging:

- 1 unit per box
- 20 units per carton

Accessories:

- 2599.972 - uvex K series hygiene kit - 2 sealing cushions, 2 noise insulating foam pads
- AC-EB - uvex earmuff bag with belt loop and hook and loop fastener, black



2599.972



AC-EB

Hearing protection Earmuffs

uvex K3 (page 2 of 2)

Product Details							
Colour		Black/Red					
Part No.		2610.003					
Design		With headband					
SLC80		33 dB, Class 5					
Clamping force		13.6N					
Weight		297g					
Packing		1 unit					
Storage		Storage location, in original packaging, dry, clean, protected from light, UV and heat. UV and heat protected in the temperature range -10°to 55 °C, humidity max. 85%. Storage period 5 years, from date of manufacture. (Date of manufacture see product or packaging) Make sure that during storage the stirrup is not stretched, and the sealing pads are not compressed.					
Life Expectancy of Product		Service life 5 years, from date of manufacture. Recommendation: Regular replacement of the sealing pads extends the service life. Dispose of the product after expiry or immediately if it is damaged or can no longer be cleaned.					
Certified standards							
AS / NZ Standards		AS/NZS 1270:2002					
European Standard		EN 352-1:2020					
American Standard		ANSI S-3.19-1974					
Attenuation Data							
Frequency in Hertz	125	250	500	1000	2000	4000	8000
Mean att. dB	19.6	21.7	33.6	38.4	37.7	37.3	41.1
Std. dev. dB	2.6	2.9	2.5	2.9	2.9	2.7	2.6
APV	17.0	18.8	31.1	35.5	34.8	34.6	38.5

Freq. - frequency
Mean att. - mean attenuation
Std. dev. - standard deviation
APV - assumed protection value

- Hearing protector Class 4 tested to AS/NZS 1270. When selected, used and maintained as specified in AS/NZS 1269, this protector may be used in noise up to **105dB(A)** assuming an **85 dB(A)** criterion. A lower criterion may require a higher protector class.

UVEX SAFETY AUSTRALIA LIMITED PARTNERSHIP

Unit 3 Riverside Centre, 24-28 River Road West, Parramatta NSW 2150, Australia
T 1800 815 790 E info@uvex.com.au
uvex-safety.com.au

UVEX Safety New Zealand Ltd

T +64 800 698 839 E info@uvex.co.nz
uvex-safety.co.nz



CLICK HERE or
SCAN QR code
for more information on
uvex hearing range