

Hearing protection Ear Plugs



XF-DT

SLC⁸⁰
dB
26

uvex x-fit detectable

- Disposable earplugs coloured blue with metal components for easy detection
- Ideal for the food and pharmaceutical industries
- Optimum for environment requiring high noise reduction
- Comfortable to wear for long periods of time
- Corded design for added safety and convenience
- Compliant to AS/NZS1270:2002; SLC⁸⁰ 26dB Class 5

Ear canal sizing:



Product Details	
Part No.	XF-DT
Barcode	4031101340562
Packaging	1 box (100 pairs corded)
SLC ⁸⁰	26 dB, Class 5
AS / NZ Standards	AS/NZS 1270:2002
Storage	If the product is stored in a dry, clean environment, away from UV light and out of direct sunlight at a temperature of -20°C to +50°C and air humidity of a maximum of 90% and storage instructions have been followed, the product can be stored for up to 5 years from the date of manufacturing. The date of manufacturing can be found on the packaging
Life Expectancy of Product	20 times / 150 hours

Attenuation Data Freq. - frequency Mean att. Mean attenuation Std. dev. – standard deviation APV – assumed protection value							
Frequency in hertz	125	250	500	1000	2000	4000	8000
Mean att. dB	26.0	28.2	28.7	29.0	34.6	39.5	42.3
Std. dev. dB	8.2	9.6	8.8	6.7	4.6	6.0	8.6
APV	17.7	18.6	20.0	22.3	30.1	33.5	33.7

Target Applications (but not limited to):

- Food and beverage industry
- Manufacturing & packaging industry
- Bottling plants
- Abattoirs
- Where detection of foreign materials is required i.e. MDF manufacturing

Hearing protector Class 5 tested to AS/NZS 1270. When selected, used and maintained as specified in AS/NZS 1269, this protector may be used in noise up to 110dB(A) assuming an 85 dB(A) criterion. A lower criterion may require a higher protector class.



CLICK or SCAN
for more information on
uvex hearing range